GOODYEAR
MORE DRIVEN.



GOODYEAR® CONSTRUCTION TIRES

THERE'S NO TIME FOR DOWNTIME

A job site is a place of work, a place to get to and a place to dig in. And just like every tool, every worker and every truck, your fleet needs unparalleled dependability from its tires to make every minute count.

As construction vehicles evolve and their capabilities and duties change, Goodyear® continues to develop innovative technologies and offer rugged products that stay ahead of ever-changing needs to keep your trucks on the job and off the lift.

GET THE ADVANTAGE WITH DURASEAL TECHNOLOGY® AND PREMIUM CONSTRUCTION TIRES

The Best Defense Against Punctures

DuraSeal Technology is the world's first built-in tire sealant and is available on several Goodyear® Construction Tires. DuraSeal instantly seals tread punctures* so fleets can spend more time on the job and less time on repairs.

*Seals up to 1/4" diameter punctures in the repairable area of the tread. Does not seal sidewall punctures.

HOW IT WORKS

When a nail puncture up to 1/4" occurs in the tread area, DuraSeal instantly surrounds the nail and seals the tread puncture.

NO COMPETITION FOR TRADITIONAL TIRE SEALANTS

DuraSeal isn't messy, doesn't dry out and doesn't need to be reapplied like traditional sealants.

LOWER COST OF OWNERSHIP

DuraSeal keeps trucks on the road that might otherwise be taken out of service for repairs. Plus, with DuraSeal Technology, fleets can eliminate application, cleaning and disposal costs that can come with traditional sealants.

A MORE EFFICIENT RETREAD

DuraSeal Technology is an easy-to-see yellow substance that helps highlight puncture locations. It can also remain in the tire during the retread process, meaning DuraSeal can keep sealing tread punctures for a casing's full life cycle.

APPLICATION GUIDE

MIXED SERVICE ALL-POSITION TIRES

LOAD RANGE H LOAD RANGE L

G751™ MSA

Significant wear improvement while enhancing overall on-road tire performance

DURASEAL SIZES AVAILABLE																								
TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	144	65	8.25	11.0	279	42.0	1,067	19.6	498	497	309	24	12.5	318	68
315/80R22.5	L	9,090	4,125	130	900	8,270	3,750	130	900	161	73	9.00	12.7	323	43.1	1,095	19.9	505	484	301	24	14.0	356	68

COMPETITIVE REPLACEMENTS: MICHELIN X WORKS Z | BRIDGESTONE M853

NON-DURASEAL SIZES AVAILABLE																								
TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	135	61	8.25	11.0	279	42.0	1,067	19.6	498	497	309	24	12.5	318	68
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	150	68	9.00	11.8	300	43.2	1,097	20.3	516	483	300	24	13.5	343	68
315/80R22.5	L	9,090	4,125	130	900	8,270	3,750	130	900	155	70	9.00	12.7	323	43.1	1,095	19.9	505	484	301	24	14.0	356	68
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	144	66	8.25	11.1	282	44.0	1,118	20.7	526	474	295	24	12.5	318	68
12R24.5	H	7,830	3,550	120	830	7,160	3,250	120	830	160	72	8.25	11.3	287	45.3	1,151	21.2	538	461	287	24	13.2	335	68

COMPETITIVE REPLACEMENTS: MICHELIN X WORKS Z | BRIDGESTONE M853

G731™ MSA

Improved all-around off-road performance

DURASEAL SIZES AVAILABLE																								
TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	143	65	8.25	11.0	279	42.0	1,067	19.6	498	497	309	24	12.5	318	68

COMPETITIVE REPLACEMENTS: MICHELIN X WORKS Z | BRIDGESTONE M843

NON-DURASEAL SIZES AVAILABLE																								
TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	135	61	8.25	11.0	279	42.0	1,067	19.6	498	497	309	24	12.5	318	68
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	149	68	9.00	11.8	300	43.2	1,097	20.3	516	484	301	24	13.5	343	68
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	95	43	7.50	10.0	254	37.0	940	17.4	442	561	349	22	11.3	287	68
275/70R22.5	H	6,940	3,150	125	860	6,395	2,900	125	860	109	50	7.50	10.6	269	38.1	968	17.7	450	545	339	23	11.9	302	68
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	144	65	8.25	11.1	282	44.0	1,118	20.7	526	474	295	24	12.5	318	68

COMPETITIVE REPLACEMENTS: MICHELIN X WORKS Z | BRIDGESTONE M843

G288 MSA®

Outstanding performance in off-highway rough road conditions

DURASEAL SIZES AVAILABLE																								
TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	146	66	8.25	11.1	282	44.0	1,118	20.7	526	474	295	25	12.5	318	68

COMPETITIVE REPLACEMENTS: MICHELIN XTY2 | BRIDGESTONE M857

NON-DURASEAL SIZES AVAILABLE																								
TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	92	42	7.50	10.0	254	36.9	937	17.3	439	563	350	22	11.3	287	68
TUBE TYPE TIRES ON TYPE I, TYPE II OR TYPE III RIMS																								
12.00R24	J	9,370	4,250	120	830	8,540	3,875	120	830	177	80	8.50	12.2	310	48.6	1,234	22.7	577	430	267	25	14.1	358	62

COMPETITIVE REPLACEMENTS: MICHELIN XTY2 | BRIDGESTONE M857

G296™ MSA

Super single tire offering long mileage for heavy on- and off-road applications

DURASEAL SIZES AVAILABLE																								
TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
425/65R22.5	L	11,400	5,150	120	830	N/A	N/A	N/A	N/A	196	89	12.25	16.3	414	44.4	1,128	20.6	523	468	291	23	N/A	N/A	68

COMPETITIVE REPLACEMENTS: MICHELIN XZY3 | BRIDGESTONE M854

NON-DURASEAL SIZES AVAILABLE																								
TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
385/65R22.5	J	9,370	4,250	120	830	N/A	N/A	N/A	N/A	169	76	11.75	14.9	378	42.5	1,080	19.8	503	488	303	23	N/A	N/A	68
425/65R22.5	L	11,400	5,150	120	830	N/A	N/A	N/A	N/A	183	83	12.25	16.3	414	44.4	1,128	20.6	523	468	291	23	N/A	N/A	68
445/65R22.5	L	12,300	5,600	120	830	N/A	N/A	N/A	N/A	206	93	13.00	17.5	445	45.5	1,156	20.9	531	457	284	23	N/A	N/A	68

COMPETITIVE REPLACEMENTS: MICHELIN XZY3 | BRIDGESTONE M854

WORKHORSE MSA

Superior over-the-road performance

TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	120	54	8.25	11.0	279	41.7	1,059	19.5	495	498	310	22	12.5	318	68
315/80R22.5	L	10,200	4,625	130	900	9,090	4,125	130	900	142	64	9.00	12.5	318	43.0	1,092	19.9	505	483	300	23	13.8	351	68
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	135	61	8.25	11.0	279	43.7	1,110	20.4	518	475	295	22	12.5	318	68
12R24.5	H	7,830	3,550	120	830	7,160	3,250	120	830	150	68	8.25	11.3	287	45.1	1,146	21.1	536	461	287	22	13.2	335	68

COMPETITIVE REPLACEMENTS: CONTINENTAL HSC1 | BFGOODRICH CROSS CONTROL S | FIRESTONE FS820

APPLICATION GUIDE

ALL-POSITION TIRES (DUNLOP®)

SP 231A™

All-position super single

TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
385/65R22.5	J	9,370	4,250	120	830	N/A	N/A	N/A	N/A	161	73	11.75	15.3	389	42.2	1,072	19.6	498	492	306	20	N/A	N/A	75

COMPETITIVE REPLACEMENTS: CONTINENTAL HTC1 | BFGOODRICH CROSS CONTROL S | FIRESTONE FS818

SP 281™

All-position super single

TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
425/65R22.5	L	11,400	5,150	120	830	N/A	N/A	N/A	N/A	190	86	12.25	16.6	422	44.5	1,130	20.5	521	469	291	24	N/A	N/A	68

COMPETITIVE REPLACEMENTS: CONTINENTAL HTC1 | BFGOODRICH CROSS CONTROL S | FIRESTONE FS818

SP 831™

Mixed-service all-position tire for on- and off-road

TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	91	41	7.50	10.0	254	36.5	927	17.0	432	569	354	19	11.3	287	68

APPLICATION GUIDE

MIXED SERVICE DRIVE TIRES

ARMOR MAX PRO GRADE MSD

Versatile, long-lasting tire for rugged mixed service applications

DURASEAL SIZES AVAILABLE																									
TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	147	67	8.25	11.0	279	42.5	1,080	19.9	505	491	305	32	12.5	318	68
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	155	70	8.25	11.0	279	44.6	1,133	20.8	528	468	291	32	12.5	318	68

COMPETITIVE REPLACEMENTS: MICHELIN X WORKS XDY | BRIDGESTONE L320

NON-DURASEAL SIZES AVAILABLE																									
TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	
TUBELESS TIRES ON 15° DROP CENTER RIMS																									
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	141	64	8.25	11.0	279	42.5	1,080	19.9	505	491	305	32	12.5	318	68
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	154	70	9.00	11.5	292	43.8	1,113	20.5	521	477	296	33	13.5	343	68
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	149	68	8.25	11.0	279	44.6	1,133	20.8	528	468	291	32	12.5	318	68

COMPETITIVE REPLACEMENTS: MICHELIN X WORKS XDY | BRIDGESTONE L320

G282 MSD®

Long on- and off-highway performance

TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	136	62	8.25	11.1	282	41.9	1,064	19.6	498	498	310	28	12.5	318	75
12R22.5	H	7,390	3,350	120	830	6,780	3,075	120	830	151	68	9.00	11.7	297	43.4	1,102	20.4	518	481	299	28	13.5	343	75
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	144	65	8.25	11.1	282	43.9	1,115	20.6	523	475	295	28	12.5	318	75

COMPETITIVE REPLACEMENTS: MICHELIN X WORKS XDY | BRIDGESTONE M799

G741 MSD™

Tough traction drive tire for severe terrain

TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	136	62	8.25	11.5	292	42.7	1,085	20.0	508	489	304	33	12.5	318	68
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	144	65	8.25	11.5	292	44.7	1,135	20.9	531	467	290	33	12.5	318	68

COMPETITIVE REPLACEMENTS: MICHELIN X WORKS XDY | BRIDGESTONE L320

G278 MSD®

Tough super single tire for severe service conditions

TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
385/65R22.5	J	9,370	4,250	120	830	N/A	N/A	N/A	N/A	181	82	11.75	14.8	376	43.0	1,092	19.9	505	485	301	30	N/A	N/A	68
425/65R22.5	L	11,400	5,150	120	830	N/A	N/A	N/A	N/A	203	92	12.25	16.5	419	44.6	1,133	20.5	521	468	291	30	N/A	N/A	68
445/65R22.5	L	12,300	5,600	120	830	N/A	N/A	N/A	N/A	222	101	13.00	18.0	457	46.0	1,168	21.1	536	453	282	30	N/A	N/A	68

COMPETITIVE REPLACEMENTS: MICHELIN XZL WB | BRIDGESTONE L315

WORKHORSE MSD®

Superior mixed service all-position tire for on- and off-road performance

TIRE SIZE	LOAD RANGE	SINGLE LOAD		SINGLE INFLATION		DUAL LOAD		DUAL INFLATION		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD DEPTH	MIN. DUAL SPACING		SPEED RATING
		LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	
TUBELESS TIRES ON 15° DROP CENTER RIMS																								
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	129	58	N/A	N/A	N/A	N/A	N/A	20.0	508	490	305	31	12.5	318	62
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	137	62	N/A	N/A	N/A	N/A	N/A	20.9	531	469	291	31	12.5	318	62

COMPETITIVE REPLACEMENTS: CONTINENTAL HDC1 | BFGOODRICH CROSS CONTROL D | FIRESTONE T831

APPLICATION GUIDE

RETREADS

ALL-POSITION

G186™ MSA®

Versatile tread for severe service applications

RETREADS	SIZE	AVAILABLE WIDTH		TREAD DEPTH
		IN	MM	32NDS
UNICIRCLE®	11R22.5	8, 8½, 9	205, 215, 230	16
UNICIRCLE	11R24.5	8, 8½, 9	205, 215, 230	16
PRECURE	–	8½, 8⅞	215, 225	18

COMPETITIVE REPLACEMENTS: MICHELIN XZY | BANDAG RTP

G286™

For severe service including mining, logging, quarry and oil fields

RETREADS	SIZE	AVAILABLE WIDTH		TREAD DEPTH
		IN	MM	32NDS
PRECURE	–	8, 8¼, 8⅞, 9½, 9⅞	205, 215, 225, 240, 250	22

COMPETITIVE REPLACEMENTS: MICHELIN XZY3 | BANDAG BRSS

G296™ MSA

All-position super single tread for heavy on- and off-road applications

RETREADS	SIZE	AVAILABLE WIDTH		TREAD DEPTH
		IN	MM	32NDS
PRECURE	–	11⅜, 12⅝, 13, 13¾	290, 320, 330, 350	23

COMPETITIVE REPLACEMENTS: MICHELIN XZY3-WIDE BASE | BANDAG BRM3/BRM-WB

G686

An all-position retread for waste haul and mixed service applications

RETREADS	SIZE	AVAILABLE WIDTH		TREAD DEPTH
		IN	MM	32NDS
PRECURE	–	8½, 8⅞, 9¼, 9½, 9⅞	215, 225, 235, 240, 250	23

COMPETITIVE REPLACEMENTS: MICHELIN XZY3 | BANDAG BRM3/BRM2

G282 MSD®

Versatile tread that combines good regional performance with off-road capabilities

RETREADS	SIZE	AVAILABLE WIDTH		TREAD DEPTH
		IN	MM	32NDS
UNICIRCLE	11R22.5	8½, 9	215, 230	28
UNICIRCLE	11R24.5	8½, 9	215, 230	28
PRECURE	–	8½, 9	215, 230	26

COMPETITIVE REPLACEMENTS: MICHELIN XDY-1 | BANDAG B799

G292 WHD

High traction and long miles to removal

RETREADS	SIZE	AVAILABLE WIDTH		TREAD DEPTH
		IN	MM	32NDS
PRECURE	–	8½, 9, 9½, 9⅞, 10⅝	215, 230, 240, 250, 270	32

COMPETITIVE REPLACEMENTS: MICHELIN XDU S | BANDAG BDM2/BDM3

G278 MSD®

Tough super single drive retread for severe service conditions

RETREADS	SIZE	AVAILABLE WIDTH		TREAD DEPTH
		IN	MM	32NDS
UNICIRCLE	425/65R22.5	13⅜, 14½	340, 370	30
UNICIRCLE	445/65R22.5	15½	390	30
PRECURE	–	13, 14¼	330, 360	30

COMPETITIVE REPLACEMENTS: MICHELIN XZL | BANDAG WBSS

G677® MSD™

More miles for your hardworking fleet

RETREADS	SIZE	AVAILABLE WIDTH		TREAD DEPTH
		IN	MM	32NDS
PRECURE	–	8½, 8⅞, 9½, 9⅞	215, 225 240, 250	27

COMPETITIVE REPLACEMENTS: MICHELIN XDY | BANDAG BDM

G177™ MODIFIED

For rugged off-road conditions

RETREADS	SIZE	AVAILABLE WIDTH		TREAD DEPTH
		IN	MM	32NDS
PRECURE	–	8, 8½, 9, 9½	205, 215, 230, 240	27
PRECURE	–	9⅞, 10⅞	250, 275	32
PRECURE	–	9⅜	240	36

COMPETITIVE REPLACEMENTS: MICHELIN XDY | BANDAG BLSS

TOTAL SOLUTION

SEE HOW GOODYEAR® CAN HELP LOWER YOUR OPERATING COSTS WITH THE TOTAL SOLUTION

Trusted Products
Innovative Products
For Any Fleet Application

Nationwide Dealer Network
2,300+ Dealers In North America
Ready To Help Your Fleet

Reliable Services
Most Reliable Nationwide Roadside
Service In The Industry*

Fleet Management Tools
Tire And Retread Tracking
And Fleet Dashboard

FIND YOUR TOTAL SOLUTION
goodyeartrucktires.com

*Fleet research study, Nov. 2015, Lieberman Research Worldwide. 590-fleet sample.
Goodyear Dealer network roadside service compared to Michelin, Bridgestone and Continental.

GOODYEAR
MORE DRIVEN.

©2019 The Goodyear Tire & Rubber Company. All rights reserved.
053514 – 03/19